

# ABS

## 50 LITRE

### Anti Freeze Foam Trolley (Cartridge)



MODEL	14226
Capacity	50 Litre
Extinguishing Agent	Anti Freeze Foam
Test Standard	EN1866
Operation Method	Cartridge Operated
Propellent	N2 Cartridge
Discharge Distance	8M
Discharge Time	45SEC
Height	1140MM
Width	455MM
Depth	550MM
Total Weight	80KG
Operate Temp	-20°C or -30°C (On request) to +60°C
Working Pressure	13 BAR
Test Pressure	30 BAR
Fire Rating	233 IV B
Part No.	CONTACT US

#### Information

Effective against **class A fires** involving ordinary combustible materials like wood, paper, cloth, furning, plastics, rubber, etc, usually of an organic nature, in which combustion normally takes places with the formation of glowing embers.

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

**Will not freeze in extreme cold temperatures.**

#### Instructions for use


1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. Unroll hose.

3. Pull safety pin and turn on valve.

4. Aim at fire and squeeze handle

Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.



Wheelmark

