


HERCULES

23KG · 45KG Carbon Dioxide Trolley



MODEL	FEM-FA-C23	FEM-FA-C45
Capacity	23 KG	45 KG
Extinguishing Agent	Carbon Dioxide	
Propellant	Carbon Dioxide	
Operating Method	Stored Pressure	
Test Standard	N/A	
Gross Weight (KG)	65	140
Operating Temperature	- 30°C to 60 °C	
Working Pressure	70 BAR	
Testing Pressure	250 BAR	
Discharge Time	≥ 25 Sec	≥ 25 Sec
Hose Length	7M	7M
Part No	FEM-FA-C23	FEM-FA-C45



Information

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

Effective against **electric fires**. Note that before attempting to fight electric fires, the electricity must be turned off.

Carbon dioxide is a **clean agent** that leaves no residue upon discharge.

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. Unroll hose.

3. Pull safety pin and turn on valve.

4. Aim at fire and squeeze handle.

Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.

Options:

- UL Approved Aluminium Cylinder (Up to 30% Lighter)
- DOT Approved Steel Cylinder
- BV Approved Steel Cylinder
- Non-Approved Steel Cylinder

