

HERCULES

50 LITRE

Foam Trolley (Stored Pressure)



MODEL	FT03-047D-00
Capacity	50 Litre
Extinguishing Agent	3% AFFF Foam
Propellant	N2
Operation Method	Stored Pressure
Test Standard	EN 1866
Discharge Time	≥ 100 SEC
Throw Distance	≥ 12M
Height	1080MM
Width	450MM
Depth	435MM
Total Weight	85.0KG
Operating Temperature	+5°C - +60°C
Working Pressure	15 BAR
Test Pressure	30 BAR
Fire Rating	A IIB
Part No.	FEM-FA-F50

Information

Effective against **class A fires** involving ordinary combustible materials like wood, paper, cloth, furning, plastics, rubber, etc, usually of an organic nature, in which combustion normally takes places with the formation of glowing embers.

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.
2. Unroll hose.
3. Pull safety pin and turn on valve.
4. Aim at fire and squeeze handle

Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.



EN3



SETSCO SG
APPROVED

