

# PROTEK 622-2

## Dual Inlet, Dual Purpose Portable Ground Monitor 622-2



### Features

- Full 3" waterway for flow rate of up to 800 GPM (3030 LPM)
- Dual swivel inlet MODEL
- Vertical travel of 63° from 12° to 75° above with inbuilt 37° safety stop from 18° to 55° above
- Carbide-tipped spikes for extended resistance to wear
- Large handle for excellent portability
- Fully enclosed worm gear is protected from the elements
- Liquid-filled pressure gauge
- Dual spring-loaded lock pins for quick and easy breakapart
- Spring-loaded forged aluminium folding legs
- Compatible with a wide range of Protek nozzles and accessories

| MODEL             | PROTEK 622-2  |
|-------------------|---|
| Flow Rate         | 1000 GPM · 3800 LPM   |
| Inlet             | 2 x 2.5" Inlet · 65mm   |
| Outlet            | 2.5" · 65mm   |
| Control           | Single hand wheel   |
| Vertical Travel   | 63° from 12° to 75° above with inbuilt<br>37° safety stop from 18° to 55° above |
| Rotational Travel | 180°  |
| Material          | Alloy   |
| Finish            | Red Powder Coating  |
| Weight            | 32 LBS · 15 KG  |
| PART NO           | NO-PRO-622-2  |

