

SYNTEX 500

Fire Hose - White Type 1















MADE IN GERMANY

Construction

- 100% High tenacity polyester yarn, circular-woven (reinforcement)
- Circular woven twill weave, warp threads multiple twisted
- High quality, very light synthetic rubber on the basis of EPDM

Features

- Absolute tough, durable & very abrasion resistant
- Seawater resistant, weather resistant
- Aging and ozone resistant
- Temperature range -40 °C up to +100 °C
- Minimum friction loss because of very smooth inner lining
- Light and flexible
- Suitable for sea water, hot water and many chemicals


DIAMETER	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT	APPROVALS	PART NO
38MM / 1.5"	20BAR	60BAR	210G	GL   	HO-T1-SSO-15
45MM / 1.75"	20BAR	60BAR	240G	GL   	HO-T1-SSO-17
52MM / 2.0"	20BAR	60BAR	290G	GL   	HO-T1-SSO-20
65MM / 2.5"	20BAR	60BAR	365G	GL 	HO-T1-SSO-25
70MM / 2.75"	20BAR	60BAR	395G	GL 	HO-T1-SSO-27
75MM / 3.0"	20BAR	60BAR	475G	GL 	HO-T1-SSO-30



Germanischer
Lloyd



DIN 14540: 2007



Wheelmark

Due to constant improvements, product dimensions may differ slightly.



FIRE ARMOUR

14 Fan Yoong Rd, Singapore 629791 T 62666788 F 62663788
Email: firearmour@firearmour.com.sg